CTM POTTERS SUPPLLIES

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Trade name : Ferro Frit 3110

Company : CTM Potters Supplies

Unit 10A, Millpark Industrial Estate

White Cross Road Woodbury Salterton Nr. Exeter EX5 1El

Telephone : 01395-233-077 Fax : 01395-233-905

E-mail address : <u>admin@ctmpotterssupplies</u>

Use of the Substance/Preparation : Ceramic coating suited for firing, for glass and ceramics.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component CAS Number EC Number % of composition

 Colemanite standard
 12291-65-5
 100%

 Ceramic frit (ground)
 65997-18-4
 100%

3. HAZARD IDENTIFICATION

Inhalation: Excessive exposure may cause symptoms of chronic lung disease.

Ingestion: The product is of low solubility in body fluids and it is likely to be of low toxicity.

Eyes: May cause physical irritation and inflammation.

Skin: The material is not a primary irritant, but as with any abrasive powder it may give rise to

minor irritation.

4. FIRST AID MEASURES

General Recommendations:

Inhalation: Remove patient to fresh air, loosen tight clothing and seek medical attention.

Ingestion: Do not induce vomiting. Seek medical advice.

Eyes: Wash immediately with copious amounts of water.

Skin: Wash affected areas with water.

5. FIRE-FIGHTING MEASURES

Extinguishing media: It is compatible with standard fire fighting technique (e.g. use of water,

carbon dioxide, dry powder, sand and chemical foam extinguishers).

Special exposure hazards: None hazard.

Protective personal equipment: None other than those suitable for the surrounding fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Leaks & Spills: Collect dry material by wet sweeping or vacuum with efficient

particulate filter.

Personal protective equipment: Respiratory protective equipment.

7. HANDLING AND STORAGE

Handling: Do not eat, drink, or smoke in areas where the material is used.

Wash thoroughly after handling the material.

Storage: Store in dry area.

8. EXPOSUIRE CONTROLS/PERSONAL PROTECTION

Engineering controls: Adequate ventilation should be provided so that Occupational Exposure

Limits are not exceeded. Local Exhaust Ventilation is normally

recommended.

Personal protective equipment: Where LEV is not practicable and exposure is likely to be excessive,

approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended

for prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: powder
Colour: off white
Odour: odourless

Flash point (⁰C): N/A

Flammability: Not known

Explosive properties: Non-explosive

Oxidising properties: None

Specific gravity: 2-3

pH value: 9.3

Melting point (⁰C): 930°C* between 900°C and 1180°C

10. STABILITY AND REACTIVITY

Chemical stability: The material is stable.

Conditions/materials to avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization products: None

11. TOXICOLOGICAL INFORMATION

Acute toxicology: LD⁵⁰ Oral (rats): >2000mg/kg

LD⁵⁰ Dermal: Not known
LD⁵⁰ inhalation: Not known

Health effects: Prolonged or repeated exposure above occupational exposure

standards may cause fibrosis of the lungs.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Not known.

Persistence: The product is chemically stable and will persist in the

environment.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with current waste disposal regulations (for UK – Control of Pollution (Special Waste Regulations 1996). Landfill is the most appropriate method.

14. TRANSPORT INFORMATION

UN/SI No. None **UN Class** Not restricted Packing Group Not restricted UK Not restricted Road **ADR** Not restricted Sea IMO Not restricted **ICAO** Not restricted Air

15. REGULATORY INFORMATION

EC Supply Labelling: None required by directive 88/379/EEC

R-Phrases: None

S-Phrases: Optional for dusty powders

S20/21 when using do not eat, drink or smoke.

S38 in case of insufficient ventilation wear suitable

respiratory equipment.

UK Occupational exposures limits*: Mg/m³ 8 hr TWA % in product.

In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitutes the user's assessment of workplace risk.

16. OTHER INFORMATION

References:

COSHH ACOP HSC approved Code of Practice for the Control of Substances Hazardous to

Health Regulations 1994

CHIP 96 Chemicals (Hazard Information and Packaging for Supply) Regulations 1996

CHIP SDS ACOPS HSC Approved Code of Practice for Safety Data Sheets in accordance with

regulation 6 of the CHIP regulations.

^{*}Refer to HSE Guidance note EH40

HSE EH40

HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSH regulations.

Further information:

Data sheet producing department: CTM Potters Supplies

Telephone: 01395-233-077

Disclaimer:

The information contained in this safety data sheet has been prepared using the best available information, however in view of technical developments, this may alter. The material must only be used for its stated purpose and the information contained within this data sheet is offered solely for use in the evaluation of this product in respect of safety, health and environmental hazards. Due to the many factors outside our control when using this product, we cannot accept liability for any injury, accident, loss or damage caused through its use.